



# CONCRETE RESURFACER SEALER



DUNLOP CONCRETE RESURFACER TINTABLE SEALER is a clear durable and hard wearing semi-gloss “wet look” sealer that protects and enhances concrete floor surfaces such as a newly applied DUNLOP CONCRETE RESURFACER and old concrete surfaces.

## COLOUR SELECTION

This sealer can be used as a clear sealer or be tinted with the DUNLOP RESURFACER SEALER TINT.

## SUITABLE SURFACES

Apply over newly applied DUNLOP CONCRETE RESURFACER, existing concrete or previously sealed concrete to provide a uniform appearance.

## SURFACE PREPARATION

Existing concrete: All concrete substrates must be structurally sound, solid, thoroughly clean and free of any release agents, paints, concrete laitance, patching compounds, dust, dirt, oils and any other contaminant that could act as a bond breaker. If necessary, mechanically prepare the floor to sound, solid concrete by shot blasting, grinding or similar. High-pressure (5000 psi) power washing may also be used to remove dust, dirt and debris, though the concrete must then be allowed to dry thoroughly before proceeding.

Acid etching, adhesive removers, solvents and sweeping compounds are not acceptable means of cleaning the substrate. The use of sanding equipment is not an effective method to remove curing and sealing compounds. Use a lawn edger to clean around walkways, paths or driveways, as well as around planter boxes and landscaped areas. Substrates must be dry for a successful application.

**Resurfaced concrete:** After application of the DUNLOP CONCRETE RESURFACER, wait a minimum of 24 hours before applying the sealer.

**New concrete:** Allow to cure for a minimum of 4-6 weeks.

**Existing concrete (unsealed):** ensure the surface is thoroughly clean and dry as per Surface Preparation.

**Previously sealed concrete (solvent or water-based sealers):** ensure the surface is thoroughly clean and dry as per Surface Preparation. Test the sealer in small

inconspicuous areas to determine suitability (penetration and adhesion).

## APPLICATION AS A CLEAR OR TINTABLE SEALER

1. Should a coloured or tinted sealer be preferred, select the desired tint. Pour the entire contents of the DUNLOP CONCRETE RESURFACER SEALER TINT (200ml) into this Sealer (3.8L).
2. Stir well before and during use with a broad paddle or lightly shake the sealed container. The product is supplied ready for use, so no thinning is required.
3. Pour into a paint tray and apply by brush, lambswool roller or a low volume spray applicator.

Do not pour the sealer directly onto the surface when applying by brush or roller. When spraying, back rolling is recommended to prevent puddles or ponding. The first coat is considered as a primer or key coat. Apply a minimum of 2 even coats; apply the second coat at right angles for best results and finish with long even strokes in the same direction. Additional coats can be applied depending on preference, wear and desired gloss level.

## DRYING AND RECOATING

Touch dry in a minimum of 2 hours and recoat once the product is touch dry. Allow a minimum of 3 hours before subjecting to foot traffic and allow a minimum of 24 hours before subjecting to vehicle traffic. Drying times will vary in cold or humid conditions.

Do not apply if windy or the surface and air temperature is under 10°C or over 32°C or if freezing temperatures could occur within 24 hours.

## COVERAGE

This product will cover approximately 8-10m<sup>2</sup> per litre, depending on surface texture or porosity.

## CLEAN UP

Clean all equipment in Xylene immediately on completion of project.



# CONCRETE RESURFACER SEALER

## SHELF LIFE

A shelf life of 12 months is expected when stored in a dry place in the original unopened packaging, at 23°C and 50% relative humidity.

## PRECAUTIONS

This sealer is flammable please refer to Safety Data. This sealer is not intended for areas with heavy traffic. Do not use in any area that will be permanently submerged. The sealer will not waterproof the surface being sealed.

This sealer is not recommended for use on smooth surfaces around swimming pools or wet areas unless the surface is textured for non-slip.

Should a non-slip surface be required the application of washed river sand can be broadcasted or sprinkled evenly over the wet sealer, followed by a second coat of sealer once the first coat has dried.

Avoid sealing driveways and paths during the heat of the day, as this may prevent penetration and adhesion of this product. Avoid sealing when dew or rain is likely.

This sealer will repel stains from spills that are cleaned up immediately. If a stain is left in place for an extended period the sealer's ability to repel the stain is reduced.

If this sealer is tinted using the DUNLOP CONCRETE RESURFACER SEALER TINT it is non-refundable, so choose your colour carefully. If the sealer has tint added, check that the colour is suitable for your requirements before it is applied. For best results and colour consistency, multiple cans of tinted product should be combined and thoroughly mixed together before starting to ensure colour uniformity.

## SAFETY DATA

**DANGER:** Flammable liquid and vapour. Harmful when in contact with skin and if inhaled. Causes eye and skin irritation (the use of Personal Protective Equipment is required). May cause drowsiness or dizziness. Do not release into the environment.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Ensure adequate ventilation during use.

Call the Poisons Information Centre on 131 126 (Aus) and 0800 764 766 (NZ) or call a doctor if you feel unwell or if swallowed.

Do not induce vomiting. Wash immediately with plenty of water if material enters the eyes. Keep out of the reach of children. Additional information is in the Material Safety Data Sheet MSDS/SDS at [www.dunlopdij.com](http://www.dunlopdij.com).

Contains: Xylene 30-60%, Ethylbenzene 1-<20% and Solvent naphtha (petroleum), light aromatic 10-<25%.  
Disposal: Do not allow material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted sealer should be kept in a sealed container, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty sealer containers.

## USER NOTES

The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of publishing. It is the responsibility of the user to ensure that the products are used in accordance with DUNLOP product instructions and in applications for which they are intended.

ARDEX Australia Pty Ltd. ABN 82 000 550 005  
7/20 Powers Road  
Seven Hills NSW 2147  
Ph: 1300 788 780  
TOLL FREE HOTLINE  
1800 222 841 (AU)

ARDEX New Zealand Ltd  
32 Lane St  
Woolston  
Christchurch NZ  
Ph: (03) 373 6900  
TOLL FREE HOTLINE  
0800 224 070 (NZ)