



**ULTIMATE**

# ENHANCING SEALER

**DUNLOP ENHANCING SEALER is a clear durable and hard wearing sealer that will protect and enhance your surface with a glossy "wet look" appearance. It has superior stain resistance to both oil and water based stains, non-yellowing and UV resistant to protect your surface to look better for longer. With the application of additional coats the surface will become glossier to your desired finish.**

## SUITABLE SURFACES

Brick, concrete, stone, slate, masonry, concrete pavers, porous tiles and cement based grouts.

Note: if you are wanting to seal your tiles, please refer to your tile supplier or tile manufacturer for suitability.

## SURFACE PREPARATION

All surfaces must be structurally sound, solid, thoroughly clean and free of any release agents, paints, sealers, concrete laitance, patching compounds, dust, dirt, oils and any other contaminant that could act as a bond breaker. The surface must be completely dry. All surface contamination and irregularities or stains existing at the time of coating will be evident and locked into the final finish.

## APPLICATION

1. Stir well before and during use with a broad paddle or lightly shake the sealed container.
2. Pour into a paint tray and apply by brush, lambswool roller or a low volume spray applicator.
3. Do not pour the sealer directly onto the surface when applying by brush or roller. When spraying, back rolling is recommended to prevent puddles or ponding.
4. Apply a minimum of 2 even coats; apply the second coat at right angles for best results and finish with long even strokes in the same direction. Additional coats can be applied depending on preference, wear and desired gloss level.

## DRYING & RECOATING

Allow a minimum of 2 hours drying time between coats. Allow a minimum of 3 hours before subjecting to foot traffic and a minimum of 24 hours before subjecting to vehicular traffic and 7 days for full cure and maximum stain resistance. Drying times will vary in cold or humid conditions. Do not apply if it is windy or the surface and air temperature is under 10°C or over 32°C or if freezing temperatures could occur within 24 hours.

## COVERAGE

This product will cover approximately 8-10m<sup>2</sup> per litre per coat, depending on surface texture or porosity.

## CLEAN UP

Clean up all equipment in Xylene immediately on completion of the project.



## PRECAUTIONS

This sealer is flammable please refer to Safety Data Sheet/SDS. This sealer is not intended for areas with heavy traffic such as commercial or industrial applications. Should a non-slip surface be required the application of washed river sand can be broadcasted or sprinkled evenly over the wet sealer, allow to dry and gently sweep away the excess sand then follow by the application of a second coat of sealer.

This sealer is not recommended for use on steel floated surfaces, high traffic (commercial) or service areas. For wet areas including swimming pool surrounds please contact our Technical Service Department.

Avoid sealing driveways and paths during the heat of the day, as this may prevent penetration and adhesion of this product. Avoid sealing when dew or rain is likely. The sealer will not waterproof the surface being sealed. Stains should be removed immediately. It is recommended to test the sealer in a small inconspicuous area to determine the suitability over the substrate for penetration and adhesion.

## SAFETY DATA

**DANGER:** Flammable liquid and vapour. Harmful when in contact with skin and if inhaled. Causes eye and skin irritation (the use of Personal Protective Equipment is required). May cause drowsiness or dizziness. Do not release into the environment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Ensure adequate ventilation during use. Call the Poisons Information Centre on 131 126 (Aus) and 0800 764 766 (NZ) or call a doctor if you feel unwell or if swallowed. Do not induce vomiting. Wash immediately with plenty of water if material enters the eyes. Keep out of the reach of children. Additional information is in the Safety Data Sheet (SDS) at [www.dunlopdiy.com](http://www.dunlopdiy.com)

**Contains:** Xylene 30-60%, Ethylbenzene 1-<20% and Solvent naphtha (petroleum), light aromatic 10-<25%.

**Disposal:** Do not allow material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted sealer should be kept in a sealed container,

0216



# ENHANCING SEALER

and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty sealer containers.

## **USER NOTES**

The technical details and recommendations contained are given in good faith and represents the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with Dunlop product instructions and in applications for which they are intended.