



QUICK-SEAL

LAMINATE JOINT SEALANT

The DUNLOP QUICK SEAL LAMINATE JOINT SEALANT is a flexible and long lasting sealant that protects self locking, glue-less laminate and timber floor boards from moisture and water damage by preventing the joints from swelling and opening. This sealant will extend the life of your floor and will keep them looking better for longer.


Use on self-locking, glue-less laminate and engineered timber floor boards in areas where moisture is prevalent such as kitchens where water is likely to be splashed.

SURFACE PREPARATION

Surfaces must be sound and dry and flooring must be as per manufacturer's instructions.

APPLICATION

1. Apply a liberal and even amount to the top of the tongue on all board edges, both sides and ends to ensure a complete seal (Some boards have a deeper groove so ensure sufficient sealant is applied). Where floor boards butt up to the kick boards in wet areas such as kitchens, apply a liberal amount to the ends of the boards to ensure a seal. Prior to application it is recommended to test a small area on the flooring edge for suitability, prior to full installation.
2. Attach or join the boards together immediately after application. Do not allow sealant to dry before joining the boards together.
3. Wait a maximum of 15-20 minutes; remove the surplus of the sealant from the top of the surface with your fingers or a plastic spatula.
4. To remove any dried sealant, wipe the area with a mild household detergent.
5. Ensure the cap is replaced tightly for future use.




STEP 1

Apply a liberal amount to the top of the tongue on all boards edges.



STEP 2

Join together immediately. Wait 15 to 20 minutes.



STEP 3

Peel dried excess sealant on top of board.



DRYING

Allow to dry for a maximum of 20 minutes. Do not apply when temperatures are below 10°C or greater than 35°C. Drying times may vary depending on surface temperature.

COVERAGE

The DUNLOP QUICK-SEAL LAMINATE JOINT SEALANT will cover approximately 10m² depending on application technique, depth of joints and porosity of the boards.

PRECAUTIONS

Do not use harsh abrasive or cleaners on the flooring as this could erode the seal. Not suitable in areas where the boards are exposed to UV conditions. Any damaged self-locking floor boards can be removed and replaced as the sealant is flexible.

SHELF LIFE

18 months when stored in the original unopened packaging in a dry place at 23°C.

SAFETY AND STORAGE

Danger. Highly flammable liquid and vapour. Causes skin irritation (the use of Personal Protective Equipment is required). May cause drowsiness or dizziness. Toxic to aquatic life.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use in a well-ventilated area. Avoid breathing vapours. Avoid release to the environment. In case of fire: Use alcohol resistant foam or normal protein foam for extinction. Keep out of reach of children.

Call the Poison Centre on 131 126 (Au) or 0800 764 766 (Nz) or call a doctor if you feel unwell. Store in a well-ventilated place. Keep container tightly closed. Check local council regarding the disposal of contents.



QUICK-SEAL

LAMINATE JOINT SEALANT

See MSDS/SDS for more information at www.dunlopdiiy.com.

Contains:
CYCLOHEXANE, 110-82-7, 5-20%. NAPHTHA PETROLEUM,
LIGHT, HYDROTREATED, 64742-49-0>50%

USER NOTES

The technical details and recommendations contained in this sheet are given in good faith and represents the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with Dunlop product instructions and in applications for which they are intended.

ARDEX Australia Pty Ltd. ABN 82 000 550 005
7/20 Powers Road
Seven Hills NSW 2147
Ph: 1300 788 780
TOLL FREE HOTLINE
1800 222 841 (AU)

ARDEX New Zealand Ltd
32 Lane St
Woolston
Christchurch NZ
Ph: (03) 373 6900
TOLL FREE HOTLINE
0800 224 070 (NZ)