



Premium

NATURAL LOOK SEALER

DUNLOP NATURAL LOOK SEALER is a water based, penetrating sealer. It maintains the natural appearance of the surface whilst offering superior stain resistance of both oil and water based stains making sealed areas easier to clean. Suitable for indoor and outdoor use with excellent UV resistance, it is suitable over a wide range of surfaces.



SUITABLE SURFACES

Brick, stone, slate, masonry, pavers, porous tiles & concrete.

SURFACE PREPARATION

All surfaces must be cleaned free from dust, dirt, grease, oil, previous surface coatings and adhesive and other surface contaminants. Any surface contamination, surface irregularities or stains existing at the time of coating will be evident and locked in to the final finish. Test sealer in a small inconspicuous area to determine suitability for the project.

APPLICATION

- 1 Apply sealer by brush, roller or a low volume spray applicator.
- 2 Care should be taken not to apply excess material in each coat. Any material that has not penetrated into the surface after 10 minutes should be removed with a cloth. The number of coats required will vary depending on the porosity of the surface. Allow 30 minutes drying time between subsequent coats.
- 3 Most surfaces will require two coats however porous surfaces may require additional coats to sufficiently seal pores.

DRYING TIME

Allow 30 minutes to 1 hour drying time between coats. Allow 24 hours curing before subjecting to light pedestrian traffic, 3 days for rubber wheeled traffic and 7 days for full cure and maximum traffic loading.

COVERAGE

1L of DUNLOP NATURAL LOOK SEALER will cover approximately 20m² per coat depending on the porosity of the surface and application technique.

CLEAN UP

Clean all equipment in warm water or water/detergent immediately on completion of project.

SHELF LIFE

A shelf life of 12 months is expected when stored in an unopened container at 23°C.

PRECAUTIONS

DUNLOP NATURAL LOOK SEALER will repel stains from spills that are cleaned up immediately. If a stain is left in place for an extended period the sealer's ability to repel the stain is reduced. The sealer will not waterproof the surface being sealed. This sealer is not recommended for use around swimming pools due to the various chemicals possibly found in swimming pools.

SAFETY

Avoid breathing in vapours and mist as well as eye and skin contact. If eye contact occurs, flush with water for at least 15 minutes and seek medical attention. Wash skin thoroughly with soap and water. If swallowed, do not induce vomiting, call doctor immediately. MSDS is available on the Dunlop Website.

USER NOTES

The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of publication. It is the responsibility of the user to ensure that the products are used in accordance with DUNLOP product instructions and in applications for which they are intended.

ARDEX AUSTRALIA PTY LTD. ABN 82 000 550 005
7/20 Powers Rd Seven Hills NSW 2147
Ph +61 2 9851 9199

ARDEX NEW ZEALAND LTD
32 Lane Street Woolston, Christchurch NZ
Ph +64 3 373 6900