



VINYL ADHESIVE

DUNLOP® VINYL ADHESIVE is a water based high strength, easy to spread adhesive for sticking vinyl sheet and vinyl tile to most concrete and timber surfaces.

SURFACE PREPARATION

Surfaces must be dry, smooth, clean and free of any contaminants that may limit adhesion to the subfloor.

Highly porous concrete or timber subfloors should be primed with DUNLOP® PRIMER AND ADDITIVE before applying adhesive.

Imperfections in the subfloor can be fixed using either DUNLOP® FLOOR LEVELLER or DUNLOP® FLOOR REPAIRERS. Refer to respective products for suitable substrate information and application instructions.

The adhesive should not be used in extremely hot or cold conditions (i.e. below 8°C or above 35°C).

APPLICATION

- 1 Apply an even coat of adhesive to the subfloor using a 1.6 x 1.6 x 1.6mm "V" notched trowel.
- 2 Allow the adhesive to become "tacky" before laying the vinyl onto the adhesive - this should take approximately 10 minutes. Tack up time will be extended in cooler conditions and shortened in warmer conditions. Do not allow the adhesive to form a skin.
- 3 Lay the vinyl onto the adhesive
- 4 Use a roller in both directions to ensure there is good transfer of adhesive to the back of the vinyl.

COVERAGE

1L of DUNLOP® VINYL ADHESIVE will cover approximately 4-5m². Coverage will vary depending on the condition of the subfloor and application technique.

CLEAN UP

Clean tools and equipment immediately after use, with warm soapy water. Dried adhesive can be removed with mineral turps.

SHELF LIFE

12 months when stored in the original unopened container at 20°C.

CAUTION

Always ensure there is adequate ventilation when using DUNLOP® VINYL ADHESIVE.

DUNLOP GUARANTEE

Product is guaranteed for 10 years when installed to manufacturer's instructions.

TOLL FREE HOTLINE

1800 222 841 (Aust)
0800 224 070 (NZ)

TECHNICAL DATA

Characteristic of Product:	
Colour:	Off White paste
Characteristic of Mix	
Mixing:	Premixed
Mix S.G:	1.3
Application Properties	(at 23°C and 50% relative humidity)
Tack Time	5-15 minutes
Setting Time:	24 hours
Application temperature:	8-35°C

USER NOTES

The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with DUNLOP product instructions and in applications for which they are intended.

Made under license

ARDEX AUSTRALIA PTY LTD. ABN 82 000 550 005
20 Powers Road, Seven Hills NSW 2147 Australia.
Ph: +61 2 9851 9199 Fax: +61 2 9674 5621

SALES OFFICES:

Sydney: Ph+61 2 9851 9100 Fax+61 2 9838 7970
Brisbane: Ph+61 7 3881 3888 Fax+61 7 3881 3188
Melbourne: Ph+61 3 9308 9255 Fax +61 3 9308 9332
Adelaide: Ph+61 8 8268 2511 Fax+61 8 8345 3207
Perth: Ph+61 8 9455 1644 Fax+61 8 9455 1227
Christchurch: Ph+64 3 384 3029 Fax+64 3 384 9779

Jan06_v1