

DUNLOP

Flexible

FC JOINTING COMPOUND



DUNLOP FC JOINTING COMPOUND is suitable for jointing fibre cement sheet and blueboard prior to coating with a decorative finish. This flexible premixed compound has excellent adhesion and is easy to use. Use DUNLOP COLOURED RENDER TEXTURE COAT as a decorative finish over fibre cement sheet or blueboard.

USE ON

Fibre Cement Sheet and Blueboard.

SURFACE PREPARATION

Ensure the surface is clean of dust, oil, grease, salt, mould, release agents or other contaminants that will interfere with adhesion. Surfaces must be dry. Protect and mask areas not being coated. Fixing of all fibre cement sheet and blueboard should be carried out as per manufacturer's instructions.

APPLICATION

Apply DUNLOP FC JOINTING COMPOUND to the sheet joint with a steel trowel. Whilst product is still wet, lay appropriate joint tape into the jointing compound. Apply a second coat of DUNLOP FC JOINTING COMPOUND over the taped joint and ensure the surface is levelled out to a feathered edge whilst the compound is still wet. When touch dry or within 4 hours, the joint finish can be lightly sanded to level off any excess jointing compound along the joints. Coverage will vary depending on the condition of the surface and site conditions.

COVERAGE

Coverage will vary depending on the condition of the surface and site conditions. As a guide, 3kg will cover approximately 21Lm and 8kg will cover approximately 56Lm at a 75mm width at a 1mm thickness.

DRYING TIME

Before application of a decorative finish allow to cure for a minimum of 1 day for each 2mm thickness of the patched render based on 23°C and 50% relative humidity. Drying times may vary in cold or humid conditions.

CLEAN UP

Clean all tools in water immediately after use.

SHELF LIFE

12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity.

PRECAUTIONS

DUNLOP FC JOINTING COMPOUND is not suitable for use over floors. Do not apply in temperatures below 10°C or above 30°C or in extreme conditions such as high wind or direct sunlight. Do not add additional water to the product.

SAFETY DATA

Keep out of the reach of children. Use gloves to prevent skin irritation and whilst sanding, avoid inhaling dust by using a dust mask. If material enters the eyes, wash immediately with plenty of water. Check with your local Council regarding the disposal of contents. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (Aus) and 0800 764 766 (NZ) or call a doctor if you feel unwell. Additional information is in the Safety Data Sheet (SDS) available at www.dunloptrade.com.au

USER NOTES

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system being employed and other products in that system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program.

Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are other-wise available to you on request. You should make yourself familiar with them.

This datasheet was issued in Nov 2018 and is valid for 3 years, unless updated sooner. Always refer to www.dunloptrade.com.au for the latest technical data from ARDEX Australia Pty. Ltd.