

MULTIPURPOSE PRIMER



DUNLOP PRIMER is a water-based primer which enhances the bond between substrates and **DUNLOP FLOOR LEVELLERS, RENDERS, TILE ADHESIVES** and **WATERPROOFING** products. Suitable substrates include new and old concrete, particleboard, marine plywood and fibre-cement sheets. **DUNLOP PRIMER** is suitable for indoor and outdoor projects over walls and floors.

SUITABLE SURFACES

Fibre-cement sheets, concrete, renders and screeds, masonry and lightweight concrete blocks, marine plywood and particleboard.

SURFACE PREPARATION

Ensure that the surface to be primed is dry, clean, free from dust, oil, grease, paint and all loose contaminating materials. Surfaces must be suitable for the subsequent product being used.

APPLICATION

SHAKE WELL BEFORE USE. Apply with sponge, brush or long nap roller over the entire surface to be primed.

For very porous substrates, a second coat is required. **DUNLOP PRIMER** must be dry prior to the application of subsequent products. Ensure that the coating is applied evenly at the recommended coverage rate of 6m²/litre.

COVERAGE

1 litre of **DUNLOP PRIMER** will cover approximately 6 square metres. Coverage will vary depending on the porosity of the surface and method of application.

DRYING TIME

DUNLOP PRIMER will be dry in approximately 15-30 minutes (at 23°C and 50% relative humidity). Drying time will vary depending on surface porosity, temperature and humidity.

STORAGE & SHELF LIFE

12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity. Store away from direct sunlight. Replace lid tightly after use. Do not empty excess primer back into the original packaging as this may cause contamination of the contents.

CLEANING

Wash brushes, sponges and rollers with clean water.

LIMITATIONS

Not suitable for use on glazed, impervious or silicone treated surfaces. Metal surfaces must be primed with an appropriate metal primer.

SAFETY

DUNLOP PRIMER is non-hazardous and non-toxic. However, the contents should not be swallowed or inhaled. In case of eye contamination, rinse with clean water and seek medical advice. Additional information is listed in the Material Safety Data Sheet (MSDS) available on the Dunlop Website www.dunlopdjy.com.

USER NOTES

The technical details and recommendations contained are given in good faith and represents the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with Dunlop product instructions and in applications for which they are intended.