



Ready-to-Go TILE-IT



DUNLOP Ready-to-Go TILE-IT is a revolutionary spray-on wall tile adhesive. Suitable for wall tiles up to 150x150mm with a non-grooved backing, DUNLOP TILE-IT is an ideal solution for indoor DIY tiling projects such as splashbacks!

SURFACE PREPARATION

Wall surfaces must be consistently flat and firmly fixed. Clean off dust, oil, grease and all loose contaminating materials or coatings. Ensure surfaces are dry, with no residue or permanent dampness. Prime all surfaces with DUNLOP PRIMER AND ADDITIVE and allow to dry.

If being applied to a new wall, allow the jointing compound to dry for 24 hours prior to the application of the primer. Do not apply over existing tiles. Not approved for use over cement block or poured cement wall.

TILE TYPES

Ceramic, stone, porcelain, glass, granite and marble tiles.

APPLICATION

1. Ensure adequate ventilation in project area. Mask the project area with painters tape and paper/plastic sheeting to protect from overspray.
2. Shake can well before use and ensure can is at room temperature at time of application.
3. Snap off blue safety tab from top of can. Hold can upright, approximately 45-60cm from the wall, aim and pull trigger.
4. Move can back and forth smoothly and evenly to achieve desired results; proper coverage should resemble a heavy frost. Avoid insufficient or heavy application of adhesive. Lightly re-spray missed areas.
5. In order to maintain a consistent spray pattern, remove any build-up of excess adhesive from spray tip. Once finished spraying, do not wipe spray tip. Leave a dried adhesive bubble, big enough to create a seal over the spray tip, until you are ready to use again.
6. Wipe any overspray off with a damp cloth. If overspray dries, remove with mineral turps.
7. Allow adhesive to dry until there is no adhesive transfer when lightly touched with fingertips. Once tacky (approximately 30 minutes), tiles can be laid for up to 1.5 hours.
8. Apply the wall tile to the surface as per manufacturer's recommendation. Press the tile firmly into the adhesive ensuring the tile is properly aligned before placing pressure on the tile. Once the tile is pressed into the adhesive, there will be very little slip and if tile is placed incorrectly, the area will need to be re-sprayed and allowed to become tacky before resetting the tile. It is recommended to draw a plan of the tiled area on the wall before applying adhesive and using tile spacers to avoid placing tiles incorrectly and having to reset the tiles.

GROUTING

The tiled area may be grouted 1 hour after installation. Remove tile spacers and use DUNLOP GROUT adding DUNLOP PRIMER & ADDITIVE to enhance colour, impart a degree of flexibility and reduce porosity and staining.

CAUTION

Contents under pressure. Store between 10°C to 49°C. AVOID FREEZING. Keep out of the reach of children. Avoid contact with skin, face or eyes. Do not ingest. PRESSURISED DISPENSER, PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 49°C. DO NOT PIERCE OR BURN, EVEN AFTER USE. Intentional misuse by deliberately concentrating and inhaling contents of aerosol containers can be harmful or fatal. DUNLOP TILE-IT must be stored at a minimum temperature of 20°C for a period of 36 hours prior to use. Failure to maintain the adhesive within this temperature range adversely affects the spray pattern, decreases coverage and reduces performance. Not to be used in areas exposed to constant heating, showers or wet areas. Suitable for wall tiling only.

FIRST AID

Skin: Remove adhesive from skin with warm soap and water.

Eye Contact: Flush eye with large quantities of water for 15 minutes and seek medical attention. If ingested, do not induce vomiting, give water to dilute, and seek medical attention immediately. DO NOT concentrate vapours and inhale fumes. Use only with proper ventilation. For advice, contact a Poisons Information Centre (13 11 26) in Australia or 0800 764 766 in New Zealand or contact a doctor.

GUARANTEE

DUNLOP products are generally warranted for 10 years when installed to relevant Australian standards, applicable DUNLOP specification, technical data sheet and instruction for application and use. While we assure customers the high standard and quality of our products and services, we accept no liability for any loss or damage which arises from particular site conditions, poor handling and storage, or installation by unqualified or unskilled applicators.

SHELF LIFE

A shelf life of 12 months is expected when stored in a dry place in original unopened container at 25°C.

DISPOSAL

Bleed off excess pressure. Please recycle the aluminium can.

Ready-to-Go TILE-IT

DIY GUIDE

1

20°C

- Store adhesive at a minimum temperature of 20°C for 24 hours prior to installation.
- Condition tile as per manufacturer's recommendations.

2

- Wipe hand across surface.
- If dust transfers, substrate is not clean.

3

- Ensure substrate, tile and surrounding areas are clean and dust free.
- Damp-wipe substrate if dust is present.
- Prime joint compound with DUNLOP PRIMER AND ADDITIVE.

4

- Protect from overspray with a spray shield, drop cloths, paper or masking.

5

- Shake aerosol can well.

6

- Remove blue safety tab.

7

- This adhesive is delivered by a low-pressure propellant. Adhesive should spray out in a wide mist and fall similar to snow towards desired surface. Avoid extremely heavy application. Refer to spray pattern photo opposite.
- Condition tile per manufacturer's recommendations.

8

COVERAGE
3.7-4.5m²
PER CAN

- Move can back and forth-spraying smoothly and evenly to achieve the results as illustrated on the packaging
- Note: spraying in a sweeping motion may result in an inconsistent spray pattern

9

- To ensure optimal spray pattern, ensure that you remove any adhesive build up that may occur during the application process.

10

- If overspray occurs, it may be removed with a damp cloth while the adhesive is still wet.

11

- Allow adhesive to dry until there is no adhesive transfer when lightly touched (approximately 30 minutes).
- High humidity and/or low temperature increases tack time.

12

- Once tacky, tiles can be laid for up to 1.5 hours, ensure that adhesive is not contaminated by dust.

TECHNICAL DATA

Chemical Type	Water based acrylic blend
Appearance	Milky white frost bubbles
Odor	Sweet mild odor
Flash Point	Will not burn
Storage	Do not subject to freezing temperatures
Shelf Life	12 months in original unopened container
Open Time	1.5 hours
Dry Time	Once adhesive is dry to touch (10-40 minutes)
VOC Content	<0.0g/ml calculated
Ready for Grouting	1 hour after application

ARDEX AUSTRALIA PTY LTD
 ABN 82 000 550 005
 7/20 Powers Rd
 SEVEN HILLS NSW 2147
 Ph +61 2 9851 9199
 Fax +61 2 9674 5621

ARDEX NEW ZEALAND LTD
 32 Lane St
 WOOLSTON CHRISTCHURCH
 Ph +64 3 373 6900
 Fax +64 3 3849 779