

TRADE RESAFLEX RAPIDSET



DUNLOP TRADE RESAFLEX RAPIDSET is a high quality, fast setting rubber modified adhesive that is suitable for grouting after just 3 hours. DUNLOP TRADE RESAFLEX RAPIDSET is suitable for ceramic wall and floor tiles in indoor and outdoor* situations. It can be used over render, plasterboard, fibre cement sheets, painted surfaces, existing tiles (indoors) and concrete in situations where minimal movement (up to 0.3mm) is anticipated. *With satisfactory drainage.

SUBSTRATES

Refer to section on Surface Preparation. Contact the DUNLOP Toll Free Service if other substrates are encountered.

TILE TYPES

Ceramic, porcelain, non-moisture sensitive stone, fully vitrified and mosaics.

COLOUR: GREY

CLASSIFICATION: C1FES1

SURFACE PREPARATION

Surfaces must be consistently flat and firmly fixed. Clean off dust, oil, grease and all loose contaminating materials. Ensure surfaces are dry before tiling, with no residue or permanent damp. Prime porous surfaces with DUNLOP PRIMER AND ADDITIVE.

CONCRETE

Should have a wood float finish. Allow at least four (4) weeks for concrete to cure prior to tiling. Screeds must be at least seven (7) days old. The surface should be true and level and pitched to drains where required. Remove any concrete sealers or curing compounds from the surface, e.g. chlorinated rubber, resin, wax sealers. Steel trowel finished concrete should be roughened mechanically to remove laitance and provide a good key for tiling.

FIBRE-CEMENT SHEET (WALLS), PLASTERBOARD AND COMPRESSED FIBRE-CEMENT SHEET FLOORS

Fix sheets according to manufacturer's instructions and prime fibre cement sheets with DUNLOP PRIMER AND ADDITIVE.

It is not necessary to prime plasterboard, however, base jointing compound must be primed with DUNLOP PRIMER AND ADDITIVE. Do not use topping compound in tiled areas. Compressed fibre cement sheet joints in indoor situations should be taped with PVC duct tape prior to tiling. Tiling over compressed fibre-cement sheet floors outdoors should be carried out as per sheet manufacturer's recommendations and Australian Standard AS 3958.

CEMENT RENDER WALLS

Render to consist of one part cement to three or four parts sand. Leave the render with a wood float finish to establish a mechanical key. Allow render at least 7 days to cure prior to tiling. It should be approximately 10mm in thickness.

PAINTED SURFACES

Water-based acrylics, PVA, polyurethanes, epoxy enamels and other finish coatings must be mechanically removed to fully expose the substrate. Where solvent-based acrylics (oil-based) are used, roughen the surface with coarse sand paper then clean the surface with warm water.

EXISTING CERAMIC TILES (INDOOR ONLY)

The existing tiles must be firm and stable. Roughen the surface of existing tiles by mechanical means and clean off contamination and dust before tiling. Ensure that at least 80% of the glaze is removed.

MIXING

1. Add 5.5-6L of clean water to a 15kg DUNLOP TRADE RESAFLEX RAPIDSET.
2. Pour water into a suitable clean plastic container. Add DUNLOP TRADE RESAFLEX RAPIDSET and mix until both elements are completely combined. Do not mix more material than can be used within the pot life (40 minutes at 23°C and 50% relative humidity).
3. Allow mixture to stand for 2 minutes. Restir before use.

APPLICATION RANGE

- Tiling practices must be in accordance with AS 3598. As a general guide, use a 6 x 6 x 6mm trowel on walls to achieve a continuous 1.5mm bed and a 10 x 10 x 10mm trowel on floors to achieve a continuous 2.5mm bed. Setting sticks are recommended when tiling walls.
- Before fixing tiles, ensure the back of the tiles are free from dust.
- Spread approximately one square metre at a time ensuring that a skin has not developed prior to bedding the tiles. Do not apply DUNLOP TRADE RESAFLEX RAPIDSET at a bed thickness greater than 10mm or less than 1.5mm.
- Press and slide the tile at right angles to the notch pattern to ensure 100% coverage on the back of the tile. Do not butt joint tiles.
- Deeply keyed quarry tiles and some extruded tiles may require buttering of the adhesive on the back of the tiles to ensure 100% coverage. Lift a tile from time to time to check that there are no voids beneath the tile. Do not spot fix tiles.
- Any surplus adhesive must be removed from the surface of the tiles and joints, before the adhesive sets.

DRYING TIME & GROUTING

Grouting may proceed as soon as the tiling has set firmly – approximately 3 hours (at 23°C and 50% relative humidity). Use DUNLOP COLOURED GROUT for joints between 1-8mm.



TRADE RESAFLEX RAPIDSET

For joints greater than 8mm use DUNLOP WIDE JOINT GROUT. Allow longer drying time for dense tiles/substrates, humid climates and low temperatures. Restrict general traffic for 24 hours after laying. Use DUNLOP PRIMER & ADDITIVE with Grout as per instructions to enhance the colour of the grout, impart a degree of flexibility and reduce porosity and staining.

MOVEMENT JOINTS

Movement joints must be in accordance with AS 3958.

COVERAGE

Coverage will vary depending on substrate condition, tile type and application technique. As a general guide, use a 6mm trowel for walls and 10mm for floors.

Trowel Size	Coverage
6mm	0.6m ² /kg
10mm	0.4m ² /kg

Size	Walls	Floors
15kg	9m ²	6m ²

SIZE

15kg

CLEAN UP

Clean tools in water immediately after use.

SHELF LIFE

9 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity.

PRECAUTIONS

- One part rubber modified adhesives generally exhibit minimum flexibility and low tolerance for movement. If unsure or where greater movement is anticipated, use DUNLOP WALL AND FLOOR TILE ADHESIVE.
- Do not use DUNLOP TRADE RESAFLEX RAPIDSET for tiling directly over timber floors. Use DUNLOP WALL & FLOOR TILE ADHESIVE over prepared sub-floor or DUNLOP TILE-ALL.
- DUNLOP TRADE RESAFLEX RAPIDSET is not suitable for fixing moisture sensitive stone or translucent tiles.
- Do not use DUNLOP TRADE RESAFLEX RAPIDSET for continuous immersion applications (swimming pools), use DUNLOP TILE-ALL or DUNLOP UNIVERSAL TILE ADHESIVE.

SAFETY DATA

This product may cause irritation and an allergic reaction to the skin. It may cause serious eye and irritation to the respiratory system. In case of contact with the eyes rinse with running water (15 mins) including removal of contaminated clothing. Wear protective gloves, clothing, eye and face protection. Avoid inhaling dust/fume/gas/mist/vapours/spray. Ensure adequate ventilation during mixing and application. Store locked up. Check with your local Council regarding the disposal of contents. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (AUS) and

0800 764 766 (NZ) or call a doctor if you feel unwell. Additional information is in the Safety Data Sheet (SDS) at www.dunlopdiiy.com.

10 YEAR GUARANTEE

Ardex Australia Pty Ltd ("we" or "us") guarantees this product (also referred to as "our goods") is free from manufacturing defects and will perform to any applicable specification published by us for 10 years from the date of application of the product if such application occurs within this product's specified shelf life. Our liability under this guarantee is limited at our option to replacement of the product, repair of any damage to the immediate surface or area of application of the product, or the cost of such replacement or repair, in each case if we are satisfied loss or damage was due to a breach of this guarantee. This guarantee does not apply if damage or loss is due to failure to follow our published instructions or any act or circumstance beyond our control, including shade variations and efflorescence and faulty workmanship on the part of any installer or applicator of the product. If you wish to make a claim under this guarantee you must notify us (address: 7/20 Powers Road Seven Hills NSW 2147; phone: 1800222841; email: technical-services@ardexaustralia.com), identify the product and provide evidence of your purchase and the subsequent application of the product within 30 days of any alleged loss or damage occurring. We reserve the right to ask you for satisfactory evidence of any alleged loss or damage and to undertake any inspections and tests necessary to establish your rights under this guarantee. Any claim under this guarantee is at your cost. This guarantee is in addition to any rights or remedies you may have as a "consumer" under the Australian Consumer Law and to that extent you need to be aware that: "Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss of damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure".

USER NOTES

The technical details and recommendations contained are given in good faith and represents the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with Dunlop product instructions and in applications for which they are intended.